


# C Pipe Plugs

C pipe plugs are used to temporarily blocking pipelines with short pipe lengths. These are produced by vulcanizing SBR+NR rubber and high-strength fabrics. It is resistant to temperatures between -30°C and +70°C. Thanks to its extra short length, it can be easily used in house pipelines and short pipe distances.

\*It can be produced with NBR rubber resistant to gas, petroleum and derivatives.



Connection Type  
( R 1/4" )



Friction Increasing  
Design



Product Code	Size Usage Range		Max. Working Pressure	Deflated Plug Dimensions		Approx. Weight
	Min. Diameter	Max. Diameter		Diameter	Total Length	
	(mm) / (inch)	(mm) / (inch)		(mm) / (inch)	(mm) / (inch)	
4016285	25 / 1"		2.5 / 36	18 / 0.7"	60 / 2.3"	0.09 / 0.01
4016286	30 / 1.2"		2.5 / 36	29 / 1.1"	60 / 2.3"	0.15 / 0.34
4016287	40 / 1.6"		2.5 / 36	37 / 1.5"	90 / 3.5"	0.15 / 0.34
4016288	50 / 2"		2.5 / 36	45 / 1.8"	110 / 4.3"	0.25 / 0.6
4016289	60 / 2.4"		2.5 / 36	58 / 2.3"	120 / 4.7"	0.35 / 0.8
4016290	75 / 3"		2.5 / 36	69 / 2.7"	140 / 5.5"	0.45 / 0.9
4016291	100 / 4"		2.5 / 36	88 / 3.5"	160 / 6.2"	0.6 / 1.3
401629250	150 / 6"		2.5 / 36	90 / 3.6"	200 / 7.8"	1.1 / 2.4
4016293	200 / 8"		2.5 / 36	138 / 5.4"	200 / 7.8"	1.6 / 3.5
4016294	250 / 10"		2.5 / 36	180 / 7.1"	250 / 9.8"	2.2 / 4.8
4016295	300 / 12"		2.5 / 36	225 / 8.9"	200 / 7.8"	3.5 / 7.1
4016296	100 / 4"	150 / 6"	2.5 / 36	88 / 3.5"	200 / 7.8"	0.7 / 1.5
4016297	150 / 6"	200 / 8"	2.5 / 36	138 / 5.4"	200 / 7.8"	2.0 / 4.4
4016298	200 / 8"	250 / 10"	2.5 / 36	180 / 7.1"	250 / 9.8"	2.9 / 6.3
4016299	250 / 10"	300 / 12"	2.5 / 36	225 / 8.9"	250 / 9.8"	3.2 / 7.0
4016300	300 / 12"	350 / 14"	2.5 / 36	280 / 11"	350 / 13.7"	4.0 / 8.8